

1 Cold and dry all in one machine

Power: 7.5~15 Kw
Displacement : 0.65~1.9 m³/min



FEATURES

①

Integrated design, greatly saving customer installation costs and use space, beautiful appearance

②

New modular structure design, compact layout; Ready-to-use, easy to move.

③

Integrated piping system reduces unit failures and leakage and greatly reduce pressure loss.

④

Direct discharge of dry compressed air, fully ensure the user terminal gas quality.

Model		XV-7.5/13Y	XV-7.5/16Y	XV-11/13Y	XV-11/16Y	XV-15/13Y	XV-15/16Y
Displacement	M³/Min	0.85	0.65	1.4	1.2	1.7	1.5
Exhaust pressure	Mpa	1.3	1.6	1.3	1.6	1.3	1.6
Power supply	V/PH/HZ	380V/50HZ					
Power	KW	7.5	7.5	11	11	15	15
External dimension (mm)	Length	1550		1970			
	Wide	700		750			
	High	1440		1664			
Weight	KG	300	300	380	380	400	400
Outlet pipe diameter	imch/mm	1"		1"		1"	

2 Platform all-in-one

Power: 7.5~15 Kw
Displacement : 0.65~1.9 m³/min



FEATURES

①

Integrated design, greatly saving customer installation costs, adopting a larger space layout, the layout is more reasonable

②

The new modular structure design adopts an enlarged air storage tank to make the air supply more stable, more energy-saving and power-saving

③

The integrated piping system reduces the possibility of unit failure and leakage, and greatly reduces pressure loss

Model		XD-7.5/13P	XD-7.5/16P	XD-11/13P	XD-11/16P	XD-15/13P	XD-15/16P
Displacement	M³/Min	0.85	0.65	1.4	1.2	1.7	1.5
Exhaust pressure	Mpa	1.3	1.6	1.3	1.6	1.3	1.6
Power supply	V/PH/HZ	380V/50HZ					
Power	KW	7.5	7.5	11	11	15	15
External dimension (mm)	Length	1900		1900			
	Wide	1350		1350			
	High	1850		1850			
Weight	KG	420	420	510	510	530	530
Outlet pipe diameter	imch/mm	1"		1"		1"	

3 Special screw air compressor

Power : 11~37 Kw
Displacement : 1.2~5.0 m³/min



FEATURES

XD series:

- ① Using high-efficiency motor direct drive screw host, high transmission efficiency,
- ② Compact structure, more convenient maintenance

XV series:

- ① The use of high-efficiency permanent magnet frequency conversion motor direct drive screw host, according to the size of the air
- ② The intelligent frequency converter is used to control the frequency of the permanent magnet

Model		XD-11/13G	XD-11/16G	XD-15/13G	XD-15/16G	XD-22/13G	XD-22/16G	XD-37/13G	XD-37/16G
Displacement	M³/Min	1.4	1.2	1.7	1.5	3.0	2.6	5.0	3.6
Exhaust pressure	Mpa	1.3	1.6	1.3	1.6	1.3	1.6	1.3	1.6
Power supply	V/PH/HZ	380V/50HZ							
Power	KW	11	11	15	15	22	22	37	37
External dimension (mm)	Length	1080			1260		1430		
	Wide	750			850		1000		
	High	1030			1160		1230		
Weight	KG	330		350		480		760	
Outlet pipe diameter	imch/mm	3/4"			1"		1-1/2"		

4 Cold and dry all in one machine with double tank
Pressure :1.6 Mpa / Displacement :2.0 m³/min

FEATURES

With double air tanks, the air volume is larger, two cooling is carried out, the air moisture is effectively precipitated, colleagues reduce the post-treatment load, extend the service life of the equipment, and reduce the center of gravity, so that the air compressor is more stable, reduce resonance, and reduce noise



汇通鑫达
HUITONG XINDA

青岛汇通鑫达空压机有限公司

Qingdao Huitong Xinda Air Compressor Co.,Ltd.

Address: No. 2, Yida Road, Nanquan Industrial Park, Jimo District, Qingdao
Tel:15315003300

**SPECIAL AIR COMPRESSOR
FOR LASER CUTTING MACHINE**

 **400 0053 338**
24-Hour Hour Hotline